


Typical Problems and Applied Treatments for a Non-fish Bearing Upgraded Stream Crossing


Problem condition (before)

- A - Diversion potential
- B - Road surface and ditch drain to stream
- C - Undersized culvert high in fill with outlet erosion



Treatment standards (after)


- A - No diversion potential with critical dip installed near hingeline
- B - Road surface and ditch disconnected from stream by rolling dip and ditch relief culvert
- C - 100-year culvert set at base of fill



Pacific Watershed Associates Inc.


Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / FAX: 707-773-1451 / www.pacificwatershed.com

Armoring Fill Faces to Upgrade Stream Crossings



Problem: Culvert set high in outboard fill has resulted in scour of the outboard fill face and natural channel.

Conditions: The existing stream crossing has a culvert sufficient in diameter to manage design stream flows and has a functional life.



Action: The area of scour is backfilled with rip-rap to provide protection in the form of energy dissipation for the remaining fill face and channel.

Treatment Specifications:




- 1) Placement of rip-rap should be between the left and right hingelines and extend from a keyway excavated below the existing channel base level at the base of the fill slope up and under the existing culvert.
- 2) Rock size and volume is determined on a site basis based on estimated discharge and existing stream bed particle size range (See accompanying road log).

Pacific Watershed Associates Inc.


Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / FAX: 707-773-1451 / www.pacificwatershed.com

PWA Typical Drawing #1b


Typical Design of a Non-fish Bearing Culverted Stream Crossing

Existing	Upgraded	Upgraded (preferred)
 <ol style="list-style-type: none"> 1. Culvert not placed at channel grade. 2. culvert does not extend past base of fill. 	 <ol style="list-style-type: none"> 1. Culvert not placed at channel grade. 2. Downspout added to extend outlet past road fill. 	 <ol style="list-style-type: none"> 1. Culvert placed at channel grade. 2. Culvert inlet and outlet rest on, or partially in, the original streambed.

Excavation in preparation for upgrading culverted crossing



Upgraded stream crossing culvert installation



Note:

Road upgrading tasks typically include upgrading stream crossings by installing larger culverts and inlet protection (trash barriers) to prevent plugging. Culvert sizing for the 100-year peak storm flow should be determined by both field observation and calculations using a procedure such as the Rational Formula.

Stream crossing culvert Installation

1. Culverts shall be aligned with natural stream channels to ensure proper function, and prevent bank erosion and plugging by debris.
2. Culverts shall be placed at the base of the fill and the grade of the original streambed, or downspouted past the base of the fill.
3. Culverts shall be set slightly below the original stream grade so that the water drops several inches as it enters the pipe.
5. To allow for sagging after burial, a camber shall be between 1.5 to 3 inches per 10 feet culvert pipe length.
6. Backfill material shall be free of rocks, limbs or other debris that could dent or puncture the pipe or allow water to seep around pipe.
7. First one end then the other end of the culvert shall be covered and secured. The center is covered last.
8. Backfill material shall be tamped and compacted throughout the entire process:
 - Base and side wall material will be compacted before the pipe is placed in its bed.
 - Backfill compacting will be done in 0.5 - 1 foot lifts until 1/3 of the diameter of the culvert has been covered. A gas powered tamper can be used for this work.
9. Inlets and outlets shall be armored with rock or mulched and seeded with grass as needed.
10. Trash protectors shall be installed just upstream from the culvert where there is a hazard of floating debris plugging the culvert.
11. Layers of fill will be pushed over the crossing until the final designed road grade is achieved, at a minimum of 1/3 to 1/2 the culvert diameter.

Erosion control measures for culvert replacement

Both mechanical and vegetative measures will be employed to minimize accelerated erosion from stream crossing and ditch relief culvert upgrading. Erosion control measures implemented will be evaluated on a site by site basis. Erosion control measures include but are not limited to:

1. Minimizing soil exposure by limiting excavation areas and heavy equipment disturbance.
2. Installing filter windrows of slash at the base of the road fill to minimize the movement of eroded soil to downslope areas and stream channels.
3. Retaining rooted trees and shrubs at the base of the fill as "anchor" for the fill and filter windrows.
4. Bare slopes created by construction operations will be protected until vegetation can stabilize the surface. Surface erosion on exposed cuts and fills will be minimized by mulching, seeding, planting, compacting, armoring, and/or benching prior to the first rains.
5. Excess or unusable soil will be stored in long term spoil disposal locations that are not limited by factors such as excessive moisture, steep slopes greater than 10%, archeology potential, or proximity to a watercourse.
6. On running streams, water will be pumped or diverted past the crossing and into the downstream channel during the construction process.
7. Straw bales and/or silt fencing will be employed where necessary to control runoff within the construction zone.


Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services

PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / Fax: 707-773-1451 / www.pacificwatershed.com

Typical Design of a Single-post Culvert Inlet Trash Rack


Cross section view



Plan view

Notes:

1. Many materials can be used for a single-post trash rack including old railroad track, galvanized pipe, and fence posts.
2. The diameter of single-post trash racks should be sized based on the size of expected woody debris. As a basic rule of thumb, the diameter of the trash rack should be equal to the diameter of the expected woody debris up to 4 inches.




Pacific Watershed Associates Inc.


Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
 PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / Fax: 707-773-1451 / www.pacificwatershed.com

Typical Design of Stream Crossing Fill Armor


Fill angles $\leq 26.5^\circ$ (2:1)




Fill angles $26.5^\circ - 35^\circ$ (1.5:1)




Fill angles $35^\circ - 45^\circ$ (1:1)



Fill angles $26.5^\circ - 35^\circ$ (1.5:1)



Fill angles $35^\circ - 45^\circ$ (1:1)



Note:

Road upgrading tasks typically include upgrading stream crossings by installing larger culverts and inlet protection (trash barriers) to prevent plugging. Culvert sizing for the 100-year peak storm flow should be determined by both field observation and calculations using a procedure such as the Rational Formula.

Stream crossing culvert Installation


1. Culverts shall be aligned with natural stream channels to ensure proper function, and prevent bank erosion and plugging by debris.
2. Culverts shall be placed at the base of the fill and the grade of the original streambed or downspouted past the base of the fill.
3. Culverts shall be set slightly below the original stream grade so that the water drops several inches as it enters the pipe.
5. To allow for sagging after burial, a camber shall be between 1.5 to 3 inches per 10 feet culvert pipe length.
6. Backfill material shall be free of rocks, limbs or other debris that could dent or puncture the pipe or allow water to seep around pipe.
7. First one end and then the other end of the culvert shall be covered and secured. The center is covered last.
8. Backfill material shall be tamped and compacted throughout the entire process:
 - Base and side wall material will be compacted before the pipe is placed in its bed.
 - Backfill compacting will be done in 0.5 - 1 foot lifts until 1/3 of the diameter of the culvert has been covered. A gas powered tamper can be used for this work.
9. Inlets and outlets shall be armored with rock or mulched and seeded with grass as needed.
10. Trash protectors shall be installed just upstream from the culvert where there is a hazard of floating debris plugging the culvert.
11. Layers of fill will be pushed over the crossing until the final designed road grade is achieved, at a minimum of 1/3 to 1/2 the culvert diameter.

Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / Fax: 707-773-1451 / www.pacificwatershed.com


Typical Dimensions Referred to for Armored Fill Crossings

Widths in oblique view



OBR - Outboard edge of road
BOT - Bottom of excavation


Lengths in profile view




Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385/ FAX: 707-773-1451/ www.pacificwatershed.com


Typical Armored Fill Crossing Installation



Cross section parallel to watercourse




Cross section perpendicular to watercourse



Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / Fax: 707-773-1451 / www.pacificwatershed.com

Ten Steps for Constructing a Typical Armored Fill Stream Crossing





Step 1

1. The two most important points are:

A) **The rock must be placed in a "U" shape across the channel to confine flow within the armored area.** (Flow around the rock armor will gully the remaining fill. Proper shape of surrounding road fill and good rock placement will reduce the likelihood of crossing failure).


B) **The largest rocks must be used to buttress the rest of the armor in two locations:** i) The base of the armored fill where the fill meets natural channel. (This will buttress the armor placed on the outboard fill face and reduce the likelihood of it washing downslope). ii) The break in slope from the road tread to the outer fill face. (This will buttress the fill placed on the outer road tread and will determine the "base level" of the creek as it crosses the road surface).



Steps 2 - 3 Lowering

2. **Remove any existing drainage structures** including culverts and Humboldt logs


3. **Construct a dip** centered at the crossing that is large enough to accommodate the 100-year flow event and prevent diversion (C-D, E-F).



Step 4 Digging Keyway

4. **Dig a keyway** (to place rock in) that extends from the outer 1/3 of the road tread down the outboard road fill to the point where outboard fill meets natural channel (up to 3 feet into the channel bed depending on site specifics) (G-H, I-J).

5. **Install geofabric (optional)** within keyway to support rock in wet areas and to prevent winnowing of the crossing at low flows.




Steps 6, 7, 8 Backfilling Keyway

6. **Put aside the largest rock** armoring to create 2 buttresses in the next step.

7. **Create a buttress using the largest rock** (as described in the site treatments specifications) at the base of fill. (This should have a "U" shape to it and will define the outlet of the armored fill.)

8. **Backfill the fill face** with remaining rock armor making sure the final armored area has "U" shape that will accommodate the largest expected flow (K-L).



Steps 9 - 10 Final armored fill





9. **Install a second buttress** at the break in slope between the outboard road and the outboard fill face. (This should define the base level of the stream and determine how deep the stream will backfill after construction) (M-N).

10. **Back fill the rest of the keyway** with the unsorted rock armor making sure the final armored area has a "U" shape that will accommodate the largest expected flow (O-P).

Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / FAX: 707-773-1451 / www.pacificwatershed.com

Typical Ditch Relief Culvert Installation



Ditch relief culvert installation




- 1) The same basic steps followed for stream crossing installation shall be employed.
- 2) Culverts shall be installed at a 30 degree angle to the ditch to lessen the chance of inlet erosion and plugging.
- 3) Culverts shall be seated on the natural slope or at a minimum depth of 5 feet at the outside edge of the road, whichever is less.
- 4) At a minimum, culverts shall be installed at a slope of 2 to 4 percent steeper than the approaching ditch grade, or at least 5 inches every 10 feet.
- 5) Backfill shall be compacted from the bed to a depth of 1 foot or 1/3 of the culvert diameter, whichever is greater, over the top of the culvert.
- 6) Culvert outlets shall extend beyond the base of the road fill (or a flume downspout will be used).
Culverts will be seated on the natural slope or at a depth of 5 feet at the outside edge of the road, whichever is less.

Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services

PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / Fax: 707-773-1451 / www.pacificwatershed.com

Typical Designs for Using Road Shape to Control Road Runoff




Outsloping Pitch for Roads Up to 8% Grade		
Road grade	Unsurfaced roads	Surfaced roads
4% or less	3/8" per foot	1/2" per foot
5%	1/2" per foot	5/8" per foot
6%	5/8" per foot	3/4" per foot
7%	3/4" per foot	7/8" per foot
8% or more	1" per foot	1 1/4" per foot

Pacific Watershed Associates Inc.


Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / Fax: 707-773-1451 / www.pacificwatershed.com

Typical Methods for Dispersing Road Surface Runoff with Waterbars, Cross-road Drains, and Rolling Dips


Waterbars (seasonal roads)



Cross-road drain and decompaction (decommissioned roads)




Rolling dips (maintained roads)



Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / Fax: 707-773-1451 / www.pacificwatershed.com

Typical Road Surface Drainage by Rolling Dips



Rolling dip installation:

1. Rolling dips will be installed in the roadbed as needed to drain the road surface.
2. Rolling dips will be sloped either into the ditch or to the outside of the road edge as required to properly drain the road.
3. Rolling dips are usually built at 30 to 45 degree angles to the road alignment with cross road grade of at least 1% greater than the grade of the road.
4. Excavation for the dips will be done with a medium-size bulldozer or similar equipment.
5. Excavation of the dips will begin 50 to 100 feet up road from where the axis of the dip is planned as per guidelines established in the rolling dip dimensions table.
6. Material will be progressively excavated from the roadbed, steepening the grade until the axis is reached.
7. The depth of the dip will be determined by the grade of the road (see table below).
8. On the down road side of the rolling dip axis, a grade change will be installed to prevent the runoff from continuing down the road (see figure above).
9. The rise in the reverse grade will be carried for about 10 to 20 feet and then return to the original slope.
10. The transition from axis to bottom, through rising grade to falling grade, will be in a road distance of at least 15 to 30 feet.

Table of rolling dip dimensions by road grade


Road grade %	Upslope approach distance (from up road start to trough) ft	Reverse grade distance (from trough to crest) ft	Depth at trough outlet (below average road grade) ft	Depth at trough inlet (below average road grade) ft
<6	55	15 - 20	0.9	0.3
8	65	15 - 20	1.0	0.2
10	75	15 - 20	1.1	0.01
12	85	20 - 25	1.2	0.01
>12	100	20 - 25	1.3	0.01

Pacific Watershed Associates Inc.


Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / Fax: 707-773-1451 / www.pacificwatershed.com

Typical Sidecast or Excavation Methods for Removing Outboard Berms on a Maintained Road


1. On gentle road segments berms can be removed continuously (see B-B').
2. On steep road segments, where safety is a concern, the berm can be frequently breached (see A-A' & B-B').
Berm breaches should be spaced every 30 to 100 feet to provide adequate drainage of the road system while maintaining a semi-continuous berm for vehicle safety.



Road cross section between berm breaches



Road cross section at berm breaches




Pacific Watershed Associates Inc.


Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / Fax: 707-773-1451 / www.pacificwatershed.com

Typical Excavation of Unstable Fillslope on an Upgraded Road

Before



After




Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / Fax: 707-773-1451 / www.pacificwatershed.com

Typical Problems and Applied Treatments for a Decommissioned Stream Crossing


Problem condition (before)

- A - Diversion potential
- B - Road surface and ditch drain to stream
- C - Undersized culvert high in fill with outlet erosion



Treatment standards (after)

- A - Diversion prevented by road surface ripping and outsloping using excavated spoils
- B - Road surface and ditch disconnected from stream by road surface decompaction and cross-road drains
- C - Stream crossing fill completely excavated




Pacific Watershed Associates Inc.


Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
 PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / Fax: 707-773-1451 / www.pacificwatershed.com

Typical Design for Road Decommissioning Treatments Employing Export and In-Place Outsloping Techniques

Export outslope (EPOS)



In-place outslope (IPOS)




Pacific Watershed Associates Inc.


Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / Fax: 707-773-1451 / www.pacificwatershed.com

Typical Excavation of Unstable Fillslope on a Decommissioned Road

Before




After



Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / Fax: 707-773-1451 / www.pacificwatershed.com

Cross-road drain and decompaction (decommissioned roads)




Cross road drain construction will ensure gullies, springs, road runoff and other concentrated flow will no longer collect over long lengths of road causing gully erosion and sediment delivery to streams. Cross road drains will be constructed at approximately 75 ft spacing intervals and these cross road drains will direct road surface runoff off the road onto stable hillslope locations.

Ripping the road surface 16 to 24 inches deep will increase road surface infiltration rates, decompact the road surface, and prevent concentrated runoff. Road ripping will also pulverize the compacted road surface or hardpan and allow for vegetation to establish and recover naturally.


Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 4433, Arcata, CA 95518 / Ph: 707-839-5130 / FAX: 707-839-8168 / www.pacificwatershed.com

Typical Rock Grade Control Structure Installation at man-made headcuts/knickpoints in a non-fish bearing stream channel



Cross section parallel and perpendicular to watercourse



Notes

The main objective is to create a structure that will not be flanked, undercut, or eroded by the stream.


The critical elements of a successful grade control structure are:

- 1) Excavating the headcut to a gentler channel gradient over a distance of stream
(See road log for details)
- 2) rock selection- rock should be selected that is resistant to transport during design flows, and has a bell shaped distribution of sizes with the median diameter equivalent to the D50 particle size of the stream at the site of installation (See road log for range of rock diameters).
- 3) The rock must be placed in a "U" shape that will contain the 100 yr. return interval stream flow, won't constrict the channel cross sectional area, and be flush with the streambed and not deflect flow.
- 4) The rock must be imbedded into the channel at least two rock diameters in thickness.
- 5) The largest rock should be used at the base and top of the grade control structure to buttress the other rock

Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 4433, Arcata, CA 95518 / Ph: 707-839-5130 / FAX: 707-839-8168 / www.pacificwatershed.com

Standard (Type 1) Rolling Dip Construction




Notes

Rolling dip type 1 existing conditions: Type 1 rolling dips are utilized when roads are less than 12-14% grade and there is proximal outfall adjacent to the outboard road to facilitate road drainage.

Design Notes:

- 1) The berm should be removed for the entire length of the dip.
- 2) The steeper the road grade the more asymmetrical the dip should be constructed, i.e. the axis of the dip should be closer to the down road side of the dip when the road gets steep. (See PWA typical drawing #11).
- 3) The dip should be outsloped at 3-4% across the road tread from start to end of each dip, and 8-10% across the outboard fill.
- 4) The dip will either connect to and drain the ditch or it will only drain the road surface, see road log for specifications.
- 5) The road tread across the dip or the outlet of the dip may be rocked depending on site specific conditions (see road log).


As-Built Features



Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 4433, Arcata, CA 95518 / Ph: 707-839-5130 / FAX: 707-839-8168 / www.pacificwatershed.com

Type 2 Rolling Dip Construction (Through-cut or thick berm road reaches)




Notes

Rolling dip type 2 existing conditions: Type 2 rolling dips are utilized when roads are less than 12-14% grade and there is no proximal outfall adjacent to the outboard road to facilitate road drainage. These should be employed in areas of road through-cuts generally less than 3 feet tall, and where large wide and/or tall berms exist on the outboard road edge.

Design Notes:

- 1) The berm or native hillside should be removed for the entire length of the excavated portion of the dip, or, at a minimum through the axis of the dip.
- 2) The steeper the road grade the more asymmetrical the dip should be constructed, i.e. the axis of the dip should be closer to the down road side of the dip when the road gets steep.
- (See PWA typical drawing #11).
- 3) The dip should be outsloped at 3-4% across the road tread and 8-10% across the outboard berm or native hillside. (The road log will specify the length of the outlet breach throughout the large berm or native hillside).
- 4) The dip will either connect to and drain the ditch or it will only drain the road surface, see road log for specifications.
- 5) The road tread across the dip or the outlet of the dip may be rocked depending on site specific conditions (see road log).

As-built Features



Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 4433, Arcata, CA 95518 / Ph: 707-839-5130 / FAX: 707-839-8168 / www.pacificwatershed.com

Type 3 Rolling Dip Construction (steep slope outslope)

Existing Conditions

Native Hillside

Cutslope

Road Tread

16%

Inboard ditch

Small Berm

Fillslope

Native Hillside

Base of fillslope

Notes

Rolling dip type 3 existing conditions: Type 3 rolling dips are utilized when roads grades are steeper than 12% grade with little opportunity to create reverse grade for the design vehicle, and there is proximal outfall adjacent to the outboard road to facilitate road drainage.

Design Notes:

- 1) The berm should be removed for the entire length of the outsloped section.
- 2) The dip should be outsloped at 2-4% across the road tread and 4-8% across the outboard fill. (The road log will specify the length of road to be type 3 outsloped).
- 3) The outsloping will rarely connect to and drain the ditch (see road log for specifications).
- 4) The road tread across the outsloped section or the outboard road will be rocked depending on site specific conditions (see road log).

Inboard ditch

Cutslope

16%

4%

8%

4%

8%

Fillslope

Base of fillslope

Native Hillside

Excavated portion of road


Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services


PO Box 4433, Arcata, CA 95518 / Ph: 707-839-5130 / FAX: 707-839-8168 / www.pacificwatershed.com

Typical Ford Crossing Installation

Oblique view



Cross-section perpendicular to watercourse




Steps for ford crossing construction:

1. Remove any existing structures (culverts, logs, large boulders, etc.)
2. Remove all road fill as you dip through the crossing to reach natural stream channel.
3. Establish a "U" shape across the channel at the width specified in the road logs.
4. Grade road approaches to specified slope angle (e.g., 4:1). Approaches may or may not be rocked; follow specifications in the road logs.

Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953/ Ph: 707-773-1385 / FAX: 707-773-1451/ www.pacificwatershed.com

Typical Design for De-watering Streams



Stream crossing de-watering


Prior to working in and around the active stream channel, proper stream dewatering and avoidance of increasing downstream turbidity should be employed. Stream flows will be isolated upstream of the work area using cofferdams and transported downstream / around the work site through either a pumped diversion (Type 1) or by gravity diversion (Type 2) to keep the stream "live" (flowing) below the work area. An additional dam will be installed downstream of the work areas to capture any subsurface flow that might travel through the construction area. Any "dirty" water will be collected at this location and pumped away from the site where it can infiltrate into the ground without the potential of delivery to the stream and/or be used to wet fill being deposited in the spoil disposal areas.

Pacific Watershed Associates Inc.


Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385/ FAX: 707-773-1451/ www.pacificwatershed.com

Typical design drawings of spring box and vaulted screened intake gravity diversion infrastructure

Piped spring box - gravity system



Vaulted screened intake - gravity system




Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / FAX: 707-773-1451 / www.pacificwatershed.com


PWA Typical Drawing #22

Typical design drawings of spring boxes

Piped spring box - gravity system



Perforated spring box - pumped system



Pacific Watershed Associates Inc.

Geologic and Geomorphic Studies • Watershed Restoration • Wildland Hydrology • Erosion Control • Environmental Services
PO Box 2070, Petaluma, CA 94953 / Ph: 707-773-1385 / FAX: 707-773-1451 / www.pacificwatershed.com

PWA Typical Drawing #23